

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN THE APPLICATION OF:	CONF. NO.:	4980
STEPHEN J. BENNISON ET. AL.	CASE NO.:	AD6926USPCT
SERIAL NO.: 10/525,704	GROUP ART UNIT:	1773
FILED: FEBRUARY 18, 2005	EXAMINER:	NAKARANI
FOR: POLYVINYLBUTYRAL INTERLAYERS HAVING SUPERIOR ACOUSTICAL PROPERTIES AND METHOD OF PREPARING SAME		

DECLARATION UNDER 37 CFR 1.132

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

I, Dr. Stephen J. Bennison, Ph.D., declare and state:

I am a named co-inventor on the subject patent application.

In 1980 I was awarded a Bachelor of Science degree (with honors) in Ceramics from the University of Leeds (Leeds, UK). My senior thesis was entitled "Microstructure-Mechanical Property Relations in a Machineable Glass Ceramic."

In 1983 I was awarded a Master of Science degree in Metallurgy and Materials Engineering from Lehigh University (Bethlehem, PA). My thesis was entitled "Grain Growth and Cavity Formation in α -Al₂O₃."

In 1987 I was awarded a Ph.D. in Materials Science and Engineering from Lehigh University. My dissertation was entitled "Effect of MgO Solute on the Sintering of High-Purity α -Al₂O₃."

I am an employee of E. I. du Pont de Nemours and Company (DuPont), the assignee of the subject patent application. Since 2007 I have been a Senior Research Associate for DuPont Packaging & Industrial Polymer Products in Wilmington, DE, where I have worked as a team leader for design with laminated glass. From 2000–2007, I was a Research Associate, DuPont Packaging & Industrial Polymer Products, in Wilmington, DE, and my responsibilities included: (a) development of glass/polymer laminates for architectural & automotive applications, with an emphasis on structural performance for building hardening, structural design, acoustic functionality and transport properties, and (b) implementation and management of modeling competency for materials design and performance specifications of laminated glass. From 1995–2000, I was a Senior Research Scientist, for the Central Research and Development department, where my duties included: (a) development of new polymer interlayers for laminated safety glazing and knowledge base for e-commerce

offering, and (b) fundamental research activities in the area of photonics and composites for dental applications. From 1992-1995, I was a Research Scientist, for the Central Research and Development department, and my responsibilities included fundamental and applied research programs addressing mechanical behavior and corrosion of materials.

DuPont is in the business of manufacturing and selling poly(vinyl butyral) (PVB) interlayers for laminated safety glass, and conducts research and development in this field. (DuPont's website states that laminated safety glass was born from research conducted in the 1930s by a consortium of companies, including DuPont, asked to find a clear, tough, adhesive material that could be manufactured efficiently into automobile windshields. (See, <http://www.dupont.com/safetyglass/en/science/history/index.html>)

Since 2003 I have been a Guest Professor for the China Building Materials Academy (CBMA) (Beijing, China).

From 1987-1991 I was a Guest Scientist, at the National Institute of Standards and Technology (NIST) (Gaithersburg, MD).

From 1980-1986 I was a Research Assistant and Teaching Assistant at Lehigh University.

I am an author or co-author of publications listed in the attachment to this Declaration.

I am named as an inventor or co-inventor on the following patents and applications:

- US 5,411,583, entitled "HF-resistant ceramics and use thereof"
- US 5,838,446, entitled "Determination of coating adhesion"
- US 7,294,397, entitled "Fibrillar microstructure for conformal contact and adhesion"
- US 2005-0042422 A1, entitled "Point attachment systems for laminated glass"
- US 2005-0266187 A1 entitled "Blast resistant glass laminates having improved" structural integrity against severe impacts"
- US 2006-0182983 A1, entitled "Thermoplastic resin compositions suitable for use in transparent laminates"
- US 2007-0289693 A1, entitled "Thermoplastic resin compositions suitable for use in transparent laminates"
- US 2007-0092706 A1, entitled "Mixed ion ionomeric sheets and high strength laminates produced therefrom"
- US 2006-0005482 A1 Point attachment systems for laminated glass and a process for preparing same"

I am involved in the following professional activities:

- Director of The American Ceramic Society (2000-2002).
- Chair Gordon Conference 2001, Solid State Studies in Ceramics.
- Vice-Chair Gordon Conference 2000, Solid State Studies in Ceramics.
- Co-organizer of focus session: *Mechanical Behavior of Layered Microstructures*, 1998 Annual Meeting of The American Ceramic Society.
- Discussion Leader, 1997 Gordon Research Conference: *Solid State Studies in Ceramics*.
- Program co-Chair of The Basic Science Division 1995 Annual Meeting of The American Ceramic Society.

- Program co-Chair of The Basic Science Division 1994 Fall Meeting - *Ceramics Manufacturing for the 21st. Century*. (American Ceramic Society).
- Co-organizer of symposium - *Fracture, Deformation and Mechanical Reliability of Ceramics*, 1993 Annual Meeting of The American Ceramic Society.
- Academic collaborations with: University of Chicago (Prof. Levi-Setti); Stanford University (Prof. Dauskardt); Imperial College London (Profs. Williams & Kinloch); Carnegie Mellon University (Prof. Saigal); University of Parma, Italy (Prof. Royer).

The claims of the subject application are focused on polyvinyl butyral (PVB) interlayers having sound-damping properties, glass laminates containing the interlayers and article containing the glass laminates. The independent claims focus on the PVB having a hydroxyl number in the range of from about 17 to about 19.5. They state that the interlayer is made with a single plasticizer in an amount in the range of from about 40 to about 50 parts per hundred (pph), wherein the plasticizer is tetraethylene glycol di heptanoate (4G7).

For instance, amended claim 1 reads:

1. An interlayer having sound-damping properties that is useful for preparing acoustic laminates, the interlayer comprising (i) polyvinyl butyral having a hydroxyl number in the range of from about 17 to about 19.5 and (ii) a single plasticizer in an amount in the range of from about 40 to about 50 parts per hundred (pph), wherein the plasticizer is tetraethylene glycol di heptanoate.


As another example, claim 15 recites:

15. An article comprising a glass laminate having sound-damping properties wherein the laminate comprises a single homogeneous interlayer of polyvinyl butyral positioned between two sheets of glass, wherein the polyvinyl butyral has a hydroxyl number in the range of from about 17 to about 19.5 and comprises a single plasticizer in an amount of from about 40 to about 50 pph parts, wherein the plasticizer is tetraethylene glycol di heptanoate.

I am aware that the claims of the subject patent application have been rejected over U.S. Patent No. 4,230,771 Phillips, which was also assigned to DuPont.

This Declaration adds data to the comparison already presented in the specification. Example 5 is newly added and shows use of a PVB interlayer representative of Phillips Example 1. Specifically, the Example 5 of the Declaration is directed to use of an interlayer comprising PVB having 23.0 % residual hydroxyl and 38.5 pph 4G7. The data is presented below.

The data in the subject patent application and Example were carried out by me or under my direction.



The above data shows that the invention provides superior damping properties and, thus, improved acoustic performance in laminated glass windows. My opinion is that increasing the plasticizer content and reducing hydroxyl amount provides a synergistic effect. Based upon my experience in the art, the data presented in the table shows that the invention provides significant advantages over the PVB interlayers, laminates and articles of the

example presented in Phillips. It is my opinion that these advantages would not be expected based upon the teachings of Phillips.

All statements made herein of my own knowledge are true, all statements made herein based on information and belief are believed to be true, and further that willful false statements and the like are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001, and may jeopardize the validity of the application or any patent issuing thereon.

Respectfully submitted,

/Dr. Stephen J Bennison/

Stephen J. Bennison

Dated: May 9, 2008

PUBLICATIONS

1. **Extending the Blast Resistance of Laminated Glass Facades**, S.J. Bennison, C.A. Smith, C.C Anderson and J.G. Sloan, in press, proceedings of the eighth international conference on architectural and automotive glass *Glass Processing Days 2003*, Tampere (Finland), to be published by Tamglass Ltd. Oy, Vehmaistenkatu 5, Tampere (Finland).
2. **Co-Planar Crack Interaction in Cleaved Mica**, J.C. Hill, S.J. Bennison, P.A. Klein, J.W. Foulk, A. Jagota, S. Saigal, *International Journal of Fracture*, in press (2003).
3. **Crack Blunting and the Strength of Soft Solids**, A. Jagota, C.Y. Hui, S.J. Bennison, J.D. Londono, *Proceedings of the Royal Society A (London)*, in press (2003).
4. **Mechanics of Adhesion Through a Fibrillar Microstructure**, Anand Jagota, Stephen J. Bennison, *Integrative and Comparative Biology*, in press (2003)
5. **Small Angle X-ray Scattering from Craze-like Structures in a Rubbery Polymer**, J.D. Londono, Anand Jagota, S.J. Bennison, R.V. Davidson, *Journal of Polymer Physics*, submitted (2002).
6. **Role of Magnesia and Silica on Microstructure Development in Alumina**, K. Gavrilov, S.J. Bennison, K.R. Mikeska, R. Levi-Setti *submitted, J. Mat. Sci.*, (2002).
7. **Rate Dependence in Viscoelastic Fracture Studied Using a Polymer Bridge in Tension**, S. Muralidhar, A. Jagota, S.J. Bennison, S. Saigal, *International Journal of Solids & Structures*, submitted (2002).
8. **Structural Performance of Laminated Glass Made with a "Stiff" Interlayer**, S.J. Bennison, C.A. Smith, A. Van Duser and A. Jagota," *Glass in Buildings*, ASTM STP 1434, V. Block, ed., American Society for Testing and Materials, West Conshohocken, PA, (2002).
9. **Computational Cohesive Zone Modeling of Polymer Interfacial Failure**, P. Rahul-Kumar, S. Muralidhar, A. Jagota, S. Bennison, S. Saigal, in *Modeling and Simulation-based Life Cycle Engineering*, K.P. Chong, S. Saigal, S. Thynell, H.S. Morgan (eds.) SPON Press (London & New York), 17-30 (2002).
10. **Mechanical Response of Cracked Laminate Plates**, S. Muralidhar, S.J. Bennison, A. Jagota and S. Saigal, *Acta*

Materialia, **50**[18] 4477-90 (2002).

11. **Structural Performance of Laminated Glass made with DuPont's SentryGlas® Plus Interlayer**, S.J. Bennison, C.A. Smith, A. Van Duser and A. Jagota, *International Glass Review*, **1** 46-50 (2002).
12. **Influence of Cohesive Zone Parameters on an Instability During Cleavage of Mica**, J. Hill, S.J. Bennison, P.A. Klein, A. Jagota, S. Saigal, In: *Proc. 10th Intl. Conf. Frac.* In press (2001).
13. **Gecko Feet Viewed from the Perspective of Elastomeric Adhesion**, A. Jagota and S.J. Bennison, *American Zoologist*, **41**[6] 1483 (2001).
14. **Strength of Laminated Safety Glass**, S.J. Bennison, C.A. Smith, A. Van Duser, A. Jagota, proceedings of the seventh international conference on architectural and automotive glass *Glass Processing Days 2001*, Tampere (Finland), published by Tamglass Ltd. Oy, Vehmaistenkatu 5, Tampere (Finland).
15. **Structural Performance of Laminated Safety Glass Made with "Stiff" Interlayers**, S.J. Bennison, C.A. Smith, A. Van Duser, A. Jagota, proceedings of the seventh international conference on architectural and automotive glass *Glass Processing Days 2001*, Tampere (Finland), published by Tamglass Ltd. Oy, Vehmaistenkatu 5, Tampere (Finland).
16. **Interfacial Failures in a Compressive Shear Strength Test of Glass/Polymer Laminates**, P. Rahul-Kumar, A. Jagota, S.J. Bennison and S. Saigal, *International Journal of Solids and Structures*, **37**[48-50] 7281-7305 (2000).
17. **Mechanical Behavior in Tension of Cracked Glass Bridged by an Elastomeric Ligament**, S. Muralidhar, A. Jagota, S.J. Bennison and S. Saigal, *Acta Materialia*, **48**[18-19] 4577-88 (2000).
18. **Analysis of a Compressive Shear Test for Adhesion Between Elastomeric Polymers and Rigid Substrates**, A. Jagota, S.J. Bennison and C.A. Smith, *International Journal of Fracture* **104**[2] 105-130 (2000).
19. **Crack Stability and Strength Variability in Alumina Ceramics with Rising Toughness-Curve Behavior**, D. Kovar, S.J. Bennison and M.J. Readey, *Acta Materialia*, **48**[2] 565-78 (2000).
20. **Cohesive Element Modeling of Viscoelastic Fracture: Application to Peel Testing of Polymers**, P. Rahul-Kumar, A. Jagota, S.J. Bennison and S. Saigal, *International Journal of Solids and Structures*, **37**[13] 1873-97 (2000).

21. **Structural Performance of Laminated Safety Glass**, S.J. Bennison, P.S. Davies, A. Jagota, A. Van Duser, C.A. Smith & R.V. Foss, proceedings of *Glass Tech Asia 2000* (March 1-2, 2000, Singapore).
22. **Corrosion of Alumina in Aqueous Hydrofluoric Acid-II**, K.R. Mikeska, S.J. Bennison and S.L. Grise, *J. Am. Ceram. Soc.*, **83**[5] 1160-64 (2000).
23. **Corrosion of Alumina in Aqueous Hydrofluoric Acid-I**, K.R. Mikeska and S.J. Bennison, *J. Am. Ceram. Soc.*, **82**[12] 3561-66 (1999).
24. **Cohesive Zone Models and Finite Elements for Simulation of Polymer Interfacial Fracture**, A. Jagota, S.J. Bennison, P. Rahul Kumar, S. Saigal, proceedings of *Adhesion '99*, 15-17 September 1999, Churchill College, Cambridge UK.
25. **Mechanical Deformation and Fracture of Glass/PVB Laminates**, A. Jagota, S.J. Bennison, C.A. Smith, R.V. Foss, A. Van Duser, proceedings of the sixth international conference on architectural and automotive glass *Glass Processing Days 1999*, pp 370-374, 13-16 June 1999, Tampere (Finland), published by Tamglass Ltd. Oy, Vehmaistenkatu 5, Tampere (Finland).
26. **Energy Partitioning in Adhesion between Glass and Polyvinyl Butyral (Butacite®)**, S.J. Bennison, A. Jagota, C.A. Smith, S. Muralidhar and S. Saigal, pp 283-88 in *Adhesion '99*, 7th. *International Conference on Adhesion and Adhesives*, Sept. 15-17 (1999) Cambridge, UK. Publ. IOM Communications Ltd. (1999).
27. **Polymer Interfacial Fracture Simulations using Cohesive Elements**, P. Rahul-Kumar, A. Jagota, S.J. Bennison, S. Saigal, S. Muralidhar, *Acta Materialia*, **47**[15-16] 4161-69 (1999).
28. **Grain Boundary Chemistry of Alumina by High-Resolution Imaging SIMS**, K. Gavrilov, S.J. Bennison, K.R. Mikeska, and R. Levi-Setti, *Acta Materialia*, **47**[15-16] 4031-39 (1999).
29. **Structural Performance of Laminated Building Glass**, R.V. Foss, A. Jagota, S.J. Bennison, A. Van Duser, C.A. Smith, proceedings of international conference on glass in buildings, University of Bath 3 April 1999.
30. **Fracture of Glass/Polyvinyl Butyral (Butacite®) Laminates in Biaxial Flexure**, S.J. Bennison, A. Jagota and C.A. Smith, *J. Am. Ceram. Soc.* **82**[7] 1761-70 (1999).
31. **Silica and Magnesia Dopant Distributions in Alumina by High**

- Resolution Scanning Secondary Ion Mass Spectrometry**, K. Gavrilov, S.J. Bennison, K.R. Mikeska, J.M. Chabala and R. Levi-Setti, *J. Am. Ceram. Soc.*, **82**[4] 1001-1008 (1999).
32. **Analysis of Glass/Polyvinyl Butyral Laminates Subjected to Uniform Pressure**, A. Van Duser, A. Jagota and S.J. Bennison, *Journal of Engineering Mechanics, ASCE*, **125**[4] 435-42 (1999).
33. **Quantification of Coating Adhesion using Laser Induced Decohesion Spectroscopy**, J.S. Meth, D. Sanderson, C. Mutchler and S.J. Bennison, *J. Adhesion*, **68**[1-2] 117-42 (1998).
34. **Crack Resistance Behavior in Ceramics**, S.J. Bennison, chpt. 3, pp 43-89, *Mechanical Test Methodology for Ceramic Design and Reliability*, D.C. Cranmer and D.W. Richerson, eds. Marcel Dekker Inc. (1998).
35. **Quantification of Coating Adhesion Using LIDS**, J.S. Meth, D. Sanderson, C. Mutchler and S.J. Bennison, pp. 466-68 in *Proceedings of the 21st. Annual Meeting of The Adhesion Society*, (1998).
36. **Subcritical Crack-Growth Behavior of Borosilicate Glass under Cyclic Loads: Evidence of a Mechanical Fatigue Effect**, S.J. Dill, S.J. Bennison and R.H. Dauskardt, *J. Am. Ceram. Soc.*, **80**[3] 773-76 (1997).
37. **Study of Grain Boundary Chemistry of Alumina Ceramics for Corrosion Resistance**, K. Gavrilov, J.M. Chabala, R. Levi-Setti, K.R. Mikeska and S.J. Bennison " *Proceedings of the XI International Conference on Secondary Ion Mass Spectrometry (SIMS-XI)*, Orlando, FL, USA (1997).
38. **Laser Induced Decohesion Spectroscopy: a New Technique for Measuring Polymer Interfacial Adhesion**, J.S. Meth; D. Sanderson; C. Mutchler, and S.J. Bennison, *Mater. Res. Soc. Symp. Proc.*, **461**, 193-198 (1997).
39. **SIMS of Interfacial Segregation in Ceramics and Composites**, J. Chabala, K.L. Gavrilov, K.R. Mikeska, S.J. Bennison and R. Levi-Setti, *Proceedings of the Microscopy and Microanalysis '97 Meeting*, pp. 525-526 Cleveland, Ohio, August 10-14, Springer (1997).
40. **Computational Models for Brittle Fracture**, A. Jagota and S.J. Bennison, *Ceramic Transactions* (1996).
41. **Adhesion and Fracture of Sapphire-Teflon® PFA Interfaces**, S.J. Bennison, L.A. Silverman and G.A. Andrejack, *Proceedings of the EURADH '96/Adhesion '96 Conference* (Institute of Materials,

- London), pp. 439-44 (1996).
42. **Element Breaking Rules in Computational Models for Brittle Fracture**, Jagota and S.J. Bennison, *Modelling and Simulation in Materials Science and Engineering*, **3** 485-501 (1995).
43. **Spring-Network and Finite-Element Models for Elasticity and Fracture**, A. Jagota, S.J. Bennison, proceedings of a workshop on Breakdown and non-linearity in soft condensed matter, K.K. Bardhan, B.K. Chakrabarti, A. Hansen (eds), Springer-Verlag Lecture Notes in Physics (1994), conference held at the Saha Institute for Nuclear Physics, Calcutta, India, 1-9 December, 1993, page 186-201 vol. 437. (1994), Springer-Verlag (Berlin, Heidelberg, New York), ISBN 3-540-58652-0.
44. **Model for Toughness Curves in Two-Phase Ceramics: II Microstructural Variables**, N.P. Padture, J.L. Runyan, S.J. Bennison, L.M. Braun and B.R. Lawn, *J. Am. Ceram. Soc.*, 2241-47, 76[9] (1993).
45. **Model for Toughness Curves in Two-Phase Ceramics: I Theoretical Fracture Mechanics Model**, B.R. Lawn, N.P. Padture, L.M. Braun and S.J. Bennison, *J. Am. Ceram. Soc.*, 2235-40, 76[9] (1993).
46. **Flaw-Tolerance and Crack-Resistance Properties of Alumina-Aluminum Titanate Composites with Tailored Microstructures**, N.P. Padture, S.J. Bennison and H.M. Chan, *J. Am. Ceram. Soc.*, 76[9] 2312-20 (1993).
47. **Reply to Comment on 'Role of Grain size in the Strength of R-curve Properties of Alumina'**, B.R. Lawn, L.M. Braun, S.J. Bennison and R.F. Cook, *J. Am. Ceram. Soc.*, 76[7] 1900-1 (1993).
48. **Objective Evaluation of Short-Crack Toughness Curves Using Indentation Flaws: Case Study on Alumina-Based Ceramics**, L.M. Braun, S.J. Bennison and B.R. Lawn, *J. Am. Ceram. Soc.*, 75[11] 3049-57 (1992).
49. **Short-Crack T-Curves and damage Tolerance in Alumina-Based Composites**, L.M. Braun, S.J. Bennison and B.R. Lawn, pp. 156-63 in *Ceramic Engineering and Science Proceedings*, vol. 13[7,8], The American Ceramic Society, Westerville OH, USA (1992).
50. **Microstructure, Toughness Curves and Mechanical Properties of Alumina Ceramics**, S.J. Bennison, J. Rödel, S. Lathabai, P. Chantikul and B.R. Lawn, pp. 209-33 in *Toughening Mechanisms in Quasi-Brittle Materials*, S.P. Shah ed., Kluwer Academic Publishers, Dordrecht, The Netherlands (1991).

51. **Microstructure, Toughness Curves and Mechanical Properties of Alumina Ceramics**, S.J. Bennison, J. Rödel, S. Lathabai, P. Chantikul and B.R. Lawn, pp. 209-33 in *Toughening Mechanisms in Quasi-Brittle Materials*, S.P. Shah ed., Kluwer Academic Publishers, Dordrecht, The Netherlands (1991).¹
 52. **Grain Growth**, S.J. Bennison, pp. 304-12 in *Engineered Materials Handbook*, vol. 4, *Ceramics and Glasses*, ASM International® (1991).
 53. **Flaw-Insensitive Ceramics**, S.J. Bennison, N.P. Padture, J.L. Runyan and B.R. Lawn, *Phil. Mag. Lett.*, **64**[4] 191-95 (1991).
 54. **Flaw-Tolerant Al₂O₃-Al₂TiO₅ Composites**, N.P. Padture, S.J. Bennison, J.L. Runyan, J. Rödel, H.M. Chan and B.R. Lawn, pp. 715-21 in *Ceramic Transactions*, vol. 19, The American Ceramic Society, Westerville OH, USA (1991).
 55. **A Loading Device for Fracture Testing Compact-Tension Specimens in the Scanning Electron Microscope**, J. Rödel, J.F. Kelly, M.R. Stoudt and S.J. Bennison, *Scanning Microscopy*, **5**[1] 29-35 (1991).
 56. **Fabrication of Flaw Tolerant Aluminum-Titanate-Reinforced Alumina**, J.L. Runyan and S.J. Bennison, *J. Europ. Ceram. Soc.*, **7** 93-99 (1991).
 57. **Role of Grain Size on Strength and R-Curve Properties of Al₂O₃**, P. Chantikul, S.J. Bennison and B.R. Lawn, *J. Am. Ceram. Soc.*, **73**[8] 2419-27 (1990).
 58. **A History of the Role of MgO in the Sintering of Al₂O₃**, S.J. Bennison and M.P. Harmer, p. 13 in *Ceramic Transactions*, vol. 7, C.A. Handwerker, J.E. Blendell and W.A. Kaisser, eds., The American Ceramic Society, Westerville OH, USA (1990).
 59. **Effect of MgO Solute on Surface Diffusion in Sapphire and the Sintering of MgO-Doped Alumina**, S.J. Bennison and M.P. Harmer, *J. Am. Ceram. Soc.*, **73**[4] 833-37 (1990).
 60. **Role of Interfacial Grain-Bridging Sliding Friction in the Crack Resistance and Strength Properties of Nontransforming Ceramics**, S.J. Bennison and B.R. Lawn, *Acta Metall.*, **37**[10] 2659-71 (1989).
 61. **Grain-Size and R-Curve Effects in the Abrasive Wear of Alumina**, S.-J. Cho, B.J. Hockey, B.R. Lawn and S.J. Bennison, *J.*
-

- Am. Ceram. Soc.*, 72[7] 1249-52 (1989).
62. **Flaw-Tolerance in Ceramics with Rising Crack Resistance Characteristics**, S.J. Bennison and B.R. Lawn, *J. Mater. Sci.*, **24** 3169-75 (1989).
63. **Mechanism for the Role of MgO in the Sintering of Al₂O₃ Containing Small Amounts of a Liquid Phase**, C.A. Bateman, S.J. Bennison and M.P. Harmer, *J. Am. Ceram. Soc.*, 72[7] 1241-44 (1989).
64. **Effect of Heat Treatment on R-Curve Behavior in a Liquid-Phase-Sintered Alumina**, S.J. Bennison, H.M. Chan and B.R. Lawn, *J. Am. Ceram. Soc.*, 72[4] 677-79 (1989).
65. **Temperature-Dependence of Hardness of Alumina-Based Ceramics**, C.P. Alpert, H.M. Chan, S.J. Bennison and B.R. Lawn, *J. Am. Ceram. Soc.*, 71 C371 (1988).
66. **Grain Growth Kinetics for Alumina in the Absence of a Liquid Phase**, S.J. Bennison and M.P. Harmer, *J. Am. Ceram. Soc.*, **68** C22 (1985).
67. **Swelling of Hot-Pressed Al₂O₃**, S.J. Bennison and M.P. Harmer, *J. Am. Ceram. Soc.*, **68** 591 (1985).
68. **Grain Growth and Cavity Formation in MgO-Doped Al₂O₃**, S.J. Bennison and M.P. Harmer, p. 171 in *Advances in Ceramics*, vol. 6, M.F. Yan and A.H. Heuer, eds., The American Ceramic Society, Westerville OH, USA (1983).
69. **Microstructural Characterization of Abnormal Grain Growth Development in Al₂O₃**, M.P. Harmer, S.J. Bennison and C. Narayan, *Mat. Sci. Res.*, **15**, 309 (1983).
70. **Microstructural Studies of Abnormal Grain Growth Development in Al₂O₃**, S.J. Bennison and M.P. Harmer, p. 929 in *Ceramic Powders*, P. Vincenzini ed., Elsevier, Amsterdam, The Netherlands (1983).
71. **Effect of MgO Solute on the Kinetics of Grain Growth in Al₂O₃**, S.J. Bennison and M.P. Harmer, *J. Am. Ceram. Soc.*, **66** C90 (1983).